

5W MR 16 GX 5,3 - BEAM 60



TAMAÑO	MR16
PIN	GX5,3
VOLTIOS	12V AC 12V& 24V DC
COLOR	2700K, 3000K (warm white) y 6500K (cold white)
LUMEN	150LM (WW) – 180 LM (CW)
LEDS	3
TIPO DE LED	3 X 1W NICHIA
CONSUMO	5W
EQUIVALENCIA EN HALÓGENO	35W
ÁNGULO	60°

5W MR 16 GU 10/E27 BEAM 25/40/120

TAMAÑO	MR16
PIN	GU10/E27
VOLTIOS	220V (85V a 265V)
COLOR	2800K (warm white) y 6500K (cold white)
LUMEN	240LM (WW) – 270LM (CW)
LEDS	3
TIPO DE LED	3 X 1W NICHIA o CREE
CONSUMO	5W
EQUIVALENCIA EN HALÓGENO	35W
ÁNGULO	25°, 40° y 120°



5W MR 16 GZ 5,3 – BEAM 25/40/120



TAMAÑO	MR16
PIN	GZ 5,3
VOLTIOS	12VDC / 12VAC
COLOR	2800K (warm white) y 6500K (cold white)
LUMEN	240LM (WW) – 270LM (CW)
LEDS	3
TIPO DE LED	3 X 1W CREE o NICHIA
CONSUMO	5W
EQUIVALENCIA EN HALÓGENO	35W
ÁNGULO	25°, 40° y 120°